



RC2500AIU-4

Antenna Interface Unit for use
with the RC2500 ACU



Enjoy the High resolution and accuracy of resolvers as position sensors on antennas equipped with Single-Speed, 3-phase AC Motors. Allows the use of the RC2500 with virtually any antenna system.

Features

- ◆ **Compact 20" x 20" x 8" NEMA-4 Enclosure** *May be mounted directly to Uni-Strut using commonly available hardware.*
- ◆ **Simple AC Mains Disconnect** *Easily understandable by non-satellite Contract Electricians.*
- ◆ **Integrated Lightning Protection**
- ◆ **Fast Acting Emergency Stop** *Clearly Labeled, externally mounted Emergency Stop Switch has press to STOP, twist to reset operation.*
- ◆ **3HP-rated Contactors** *Azimuth and Elevation*
- ◆ **Reliable Over-Current Protection** *Adjustable, Continuous Over-Current Monitor.*
- ◆ **Single- or Three-Phase AC Polarization Drive** *Single Speed Polarization Control.*
- ◆ **Supports Electromechanical Brakes for AZ and EL axes.**
- ◆ **Flexible** *May be configured for a wide variety of Antenna Systems*
- ◆ **Optional Local Jog Control** *Simultaneous, Three-axis drive allows antenna positioning directly at the antenna for maintenance.*

SPECIFICATIONS (preliminary)

SIZE/WEIGHT/POWER

Size: 20" x 20" x 8" (Overall Dim.)
Weight: 40.0 lbs.
Mounting: Four 3/8" holes for Uni-Strut
Ambient Temperature: -20° - 40° C
Input Power: 208 VAC 3-phase, 50/60 Hz.
20-Amp Service;

PHYSICAL INTERFACES

AZ/EL/POL Motors: 1/2" conduit or cable liquid-tite fittings.
AZ/EL/POL Limit Switches: 1/2" conduit or cable liquid-tite fittings.
AZ/EL/POL Resolvers: 1/2" conduit, or cable liquid-tite fittings.
RC2500 ACU: 1" L-T Conduit fitting; (no conduit supplied)
AC Input: 1" L-T Conduit fitting; (no conduit supplied)

Research Concepts, Inc.

5420 Martindale, Shawnee, Kansas 66218 USA TEL: (913) 422-0210, FAX: (913) 422-0211

Website: WWW.ResearchConcepts.COM Email: support@researchconcepts.com